

# 3rd Quarter Emissions Testing Report 2018

OneSteel Recycling Hexham



NATA ACCREDITATION No. 2778 (14391)

Accredited for compliance with ISO/IEC 17025 – Testing

The results of the tests, calibrations and/or measurements included in this document are traceable to Australian/national standards

This document may not be reproduced except in full.

## 3rd Quarter Emissions Testing Report 2018

OneSteel Recycling Hexham

Client: OneSteel Recycling Pty Ltd

ABN: 28 002 707 262

Prepared by

**AECOM Australia Pty Ltd**

17 Warabrook Boulevard, Warabrook NSW 2304, PO Box 73, Hunter Region MC NSW 2310, Australia

T +61 2 4911 4900 F +61 2 4911 4999 www.aecom.com

ABN 20 093 846 925

16-Oct-2018


Job No.: 60493017

AECOM in Australia and New Zealand is certified to ISO9001, ISO14001 AS/NZS4801 and OHSAS18001.


© AECOM Australia Pty Ltd (AECOM). All rights reserved.

AECOM has prepared this document for the sole use of the Client and for a specific purpose, each as expressly stated in the document. No other party should rely on this document without the prior written consent of AECOM. AECOM undertakes no duty, nor accepts any responsibility, to any third party who may rely upon or use this document. This document has been prepared based on the Client's description of its requirements and AECOM's experience, having regard to assumptions that AECOM can reasonably be expected to make in accordance with sound professional principles. AECOM may also have relied upon information provided by the Client and other third parties to prepare this document, some of which may not have been verified. Subject to the above conditions, this document may be transmitted, reproduced or disseminated only in its entirety.

## Quality Information

Document 3rd Quarter Emissions Testing Report 2018  
 Ref 60493017  
 Date 10-October-2018  
 Prepared by Sharn Crosdale  
 Reviewed by Paul Wenta  
 AECOM Approved Signatory Chad Whitburn 

### Revision History

Rev	Revision Date	Details	Authorised	
			Name/Position	Signature
0	16-Oct-2018	Report for Issue	Chad Whitburn Associate Director - Compliance Services	

## Table of Contents

1.0	Introduction	1
2.0	Sampling Plane Requirements	2
3.0	Methodology	3
	3.1 NATA Accredited Methods	3
	3.2 Equipment Calibration	3
4.0	Sampling Location	4
	4.1 Sampling Location Summary	4
5.0	Results	5
Appendix A		
	Field Sheets (17 pages)	A
Appendix B		
	Laboratory Results (8 pages)	B

### List of Tables

Table 1	Criteria for Selection of Sampling Planes (AS 4323.1)	2
Table 2	AECOM NATA Endorsed Methods	3
Table 3	Sampling Location Summary	4
Table 4	Shredder Baghouse Emission Results Summary, 18 September 2018	5
Table 5	Fine Particulate (PM <sub>10</sub> ), Total Particulate and Hazardous Substance (Metals) Results, 18 September 2018	6
Table 6	Hazardous Substances (Metals) Elemental Analysis Results, 18 September 2018	7

## 1.0 Introduction

AECOM was appointed by OneSteel Recycling Pty Ltd to conduct a series of measurements to determine air emissions from the Shredder Baghouse Stack (EPL Point 1) at the Hexham facility. Measurements were required for NSW EPA licence compliance (EPL No. 5345).

Testing was undertaken on 18 September 2018 to investigate emission concentrations for the following parameters:

- Fine Particulates (PM<sub>10</sub>);
- Total Particulate (TP); and
- Hazardous Substances (Metals) including Lead and Mercury.

Laboratory analysis was undertaken by the following laboratories which hold NATA accreditation for the specified tests:

- Steel River Testing, laboratory NATA accreditation number 18079, performed the following analysis detailed in report number 16962-0-M & 16962-0-P:
  - Total Particulate (TP);
  - Fine Particulates (PM<sub>10</sub>); and
  - Moisture.
- SGS Australia Pty Ltd, NATA accreditation number 2562, performed the following analysis detailed in report number ME308220 R0:
  - Hazardous Substances (Metals).

## 2.0 Sampling Plane Requirements

The criteria for sampling planes are specified in AS 4323.1-1995 (R2014).

**Table 1 Criteria for Selection of Sampling Planes (AS 4323.1)**

Type of flow disturbance	Minimum distance upstream from disturbance, diameters (D)	Minimum distance downstream from disturbance, diameters (D)
Bend, connection, junction, direction change	>2D	>6D
Louvre, butterfly damper (partially closed or closed)	>3D	>6D
Axial fan	>3D	>8D (see Note)
Centrifugal fan	>3D	>6D

*NOTE: The plane should be selected as far as practicable from a fan. Flow straighteners may be required to ensure the position chosen meets the check criteria listed in Items (a) to (f) below.*

- a. *The gas flow is basically in the same direction at all points along each sampling traverse;*
- b. *The gas velocity at all sampling points is greater than 3 m/s;*
- c. *The gas flow profile at the sampling plane shall be steady, evenly distributed and not have a cyclonic component which exceeds an angle of 15° to the duct axis, when measured near the periphery of a circular sampling plane;*
- d. *The temperature difference between adjacent points of the survey along each sampling traverse is less than 10% of the absolute temperature, and the temperature at any point differs by less than 10% from the mean;*
- e. *The ratio of the highest to lowest pitot pressure difference shall not exceed 9:1 and the ratio of highest to lowest gas velocities shall not exceed 3:1. For isokinetic testing with the use of impingers, the gas velocity ratio across the sampling plane should not exceed 1.6:1; and*
- f. *The gas temperature at the sampling plane should preferably be above the dewpoint.*

The sampling plane for EPL Point 1 was compliant with the AS4323.1.

## 3.0 Methodology

### 3.1 NATA Accredited Methods

The following methods are accredited with the National Association of Testing Authorities (NATA) (accreditation number 2778 (14391)) and are approved for the sampling and analysis of gases. Specific details of the methods are available on request.

All sampling and analysis is conducted according to the methods in **Table 2**.

**Table 2 AECOM NATA Endorsed Methods**

NSW EPA Approved Methods	USEPA Methods	Method Title
AS4323.1	N/A	Selection of sampling positions
AS4323.2	N/A	Determination of total particulate matter – isokinetic manual sampling – gravimetric method
NSW EPA TM-2	USEPA (2000) Method 2	Determination of stack gas velocity and volumetric flow rate (type s pitot tube)
NSW EPA TM-22	USEPA (2000) Method 4	Determination of moisture content in stack gases
NSW EPA TM-23	USEPA (2000) Method 3	Gas analysis for the determination of dry molecular weight
NSW EPA OM-5	USEPA (1997) Method 201 or 201A (as appropriate)	Determination of PM <sub>10</sub> emissions
NSW EPA TM-12,13 and 14	USEPA Method 29	Determination of metal emissions from stationary sources

All parameters are reported adjusted to 0°C at 1 atmosphere and dry gas.

### 3.2 Equipment Calibration

AECOM has a calibration schedule to ensure the emission testing equipment is maintained in good order and with known calibration. Equipment used in this project was calibrated according to the procedures and frequency identified in the AECOM calibration schedule. Details of the schedule and the calibration calculations are available on request.

## 4.0 Sampling Location

### 4.1 Sampling Location Summary

**Table 3** provides a summary of the location sampled by AECOM on 18 September 2018.

**Table 3 Sampling Location Summary**

Discharge Description	Shredder Baghouse Stack (EPL Point 1)
Duct Shape	Circular
Construction Material	Metal
Duct Diameter (mm)	760
Minimum No. Sampling Points	12
Sampling Ports	2
Min. Points/Traverse	6
Disturbance	No
Distance from Upstream Disturbance	6.6D
Type of Disturbance	Bend
Distance from Downstream Disturbance	2.6D
Type of Disturbance	Stack Exit
Ideal Sampling Location	Yes
Correction Factors Applied	No
Total No. Points Sampled	12
Points/Traverse	6
Sampling Performed to Standard <sup>1</sup>	Yes

<sup>1</sup> AS 4323.1 Section 4.1  
D = Diameters



## 5.0 Results

A summary of air emission test results is shown in **Table 4**. Detailed results along with gas stream properties during the testing period can be found in **Table 5**. Speciated Hazardous Substances (Metals) results are presented in **Table 6**. Emission concentrations are converted to standard conditions of 0°C, dry gas and 1 atm pressure for comparison with regulatory limits.

Field sheets and final calculations recorded during the project are attached as **Appendix A**. Laboratory reports can be referred to in **Appendix B**.

AECOM has a calculated limit of uncertainty in regards to results. The estimation of measurement uncertainty in source testing is conducted to provide an indication of the precision of the measurement result and a degree of confidence in the range of values the reported result may represent. The measurement of uncertainty has been calculated at  $\pm 13.6\%$ .

**Table 4 Shredder Baghouse Emission Results Summary, 18 September 2018**

Parameter	Emission Concentration (EPL Point 1)	Emission Concentration Limit
Total Particulate (TP) (mg/m <sup>3</sup> )	31	100
Fine Particulate (PM <sub>10</sub> ) (mg/m <sup>3</sup> )	2.1	N/A
Lead (mg/m <sup>3</sup> )	0.054	5
Mercury (mg/m <sup>3</sup> )	0.000062	1
Total Hazardous Substances (Metals) (mg/m <sup>3</sup> )	0.077	N/A

Results from testing conducted on EPL Point 1 on 18 September 2018 are below the regulatory limits listed in EPL 5345.

**Table 5 Fine Particulate (PM<sub>10</sub>), Total Particulate and Hazardous Substance (Metals) Results, 18 September 2018**

<b>Sampling Conditions:</b>		
Stack internal diameter at test location	760 mm	
Stack gas temperature (average)	26.4 °C	299.6 K
Stack pressure (average)	1020 hPa	
Stack gas velocity (average, stack conditions)	5.3 m/s	
Stack gas flowrate (stack conditions)	2.4 m <sup>3</sup> /s	
Stack gas flowrate (0°C, dry gas, 1 atm pressure)	2.2 m <sup>3</sup> /s	
<b>Fine Particulate (PM<sub>10</sub>) Testing</b>		
Test Period	10:45 -	12:05
Fine Particulate (PM <sub>10</sub> ) Mass	2.0 mg	
Gas Volume Sampled	0.94 m <sup>3</sup>	
Fine Particulate (PM <sub>10</sub> ) Emission* <sup>1</sup>	2.1 mg/m <sup>3</sup>	
Fine Particulate (PM <sub>10</sub> ) Mass Emission Rate* <sup>2</sup>	4.6 mg/s	
Regulatory Limit	N/A	
<b>Total Particulate Testing</b>		
Test Period	10:45 -	12:05
Total Particulate Mass	19 mg	
Gas Volume Sampled	0.62 m <sup>3</sup>	
Total Particulate Emission* <sup>1</sup>	31 mg/m <sup>3</sup>	
Total Particulate Mass Emission Rate* <sup>2</sup>	68 mg/s	
Regulatory Limit	100 mg/m <sup>3</sup>	
<b>Hazardous Substances (Metals) Testing</b>		
Test Period	10:45 -	12:05
Hazardous Substances (Metals) Mass	0.10 mg	
Gas Volume Sampled	1.3 m <sup>3</sup>	
Hazardous Substances (Metals) Emission* <sup>1</sup>	0.077 mg/m <sup>3</sup>	
Hazardous Substances (Metals) Mass Emission Rate* <sup>2</sup>	0.17 mg/s	
Regulatory Limit	N/A	
<b>Moisture Content (%)</b>	<b>1.4</b>	
<b>Gas Density (dry at 1 atmosphere)</b>	<b>1.29 kg/m<sup>3</sup></b>	
<b>Dry Molecular Weight</b>	<b>28.8 g/g-mole</b>	

Notes \*1 Emission concentration at Standard conditions of 0°C, 1 atm, dry gas

\*2 Mass emission rate determined from pre and post-test sampling flow measurements and the respective test moisture content. See Q<sub>std</sub> in field sheets and final calculations "Stack Analysis - Final Calculations" for each test.

Table 6 Hazardous Substances (Metals) Elemental Analysis Results, 18 September 2018

Sample	Total Particulate Metals (mg)	Total Particulate Metals (mg/m <sup>3</sup> )	Total Gaseous Metals (mg)	Total Gaseous Metals (mg/m <sup>3</sup> )	Total Oxidisable Mercury (mg)	Total Oxidisable Mercury (mg/m <sup>3</sup> )	Total (mg)	Total (mg/m <sup>3</sup> )	Mass Emission Rate (mg/s)
Antimony	0.0011	0.000845	0.00055	0.000423			0.0017	0.00131	0.00287
Arsenic	0.00046	0.000353	0.0003	0.00023			0.00076	0.000584	0.00128
Beryllium	0.00002	0.0000154	0.0002	0.000154			0.00022	0.000169	0.00037
Cadmium	0.00206	0.00158	0.0001	0.0000768			0.0022	0.00169	0.0037
Chromium	0.0026	0.002	0.0004	0.000307			0.003	0.0023	0.00503
Cobalt	0.00049	0.000376	0.0003	0.00023			0.00079	0.000607	0.00133
Copper	0.00605	0.00465	<0.0001	<0.0000768			0.0061	0.00469	0.0103
Lead	0.0683	0.0525	0.0018	0.00138			0.07	0.0538	0.118
Magnesium	0.0472	0.0363	0.0138	0.0106			0.061	0.0469	0.103
Manganese	0.0089	0.00684	0.0082	0.0063			0.017	0.0131	0.0287
Mercury	0.00003	0.000023	<0.0001	<0.0000768	0.0000513	0.0000394	0.000081	0.0000622	0.000136
Nickel	0.00195	0.0015	<0.0001	<0.0000768			0.002	0.00154	0.00337
Selenium	<0.00081	<0.000622	0.0004	0.000307			0.0004	0.000307	0.000672
Thallium	0.0004	0.000307	0.00025	0.000192			0.00065	0.000499	0.00109
Tin	0.00174	0.00134	<0.0161	<0.0124			0.0017	0.00131	0.00287
Vanadium	<0.0042	<0.00323	<0.005	<0.00384			<0.0001	<0.0000768	<0.000168
Zinc	0.46	0.353	0.0209	0.0161			0.48	0.369	0.807
<b>Total Hazardous Metals*</b>	<b>0.0863</b>	<b>0.0663</b>	<b>0.0125</b>	<b>0.0096</b>	<b>0.0000513</b>	<b>0.0000394</b>	<b>0.101</b>	<b>0.077</b>	<b>0.169</b>
<b>Total Metals</b>	<b>0.601</b>	<b>0.462</b>	<b>0.0472</b>	<b>0.0363</b>			<b>0.648</b>	<b>0.498</b>	<b>1.09</b>

\* Total does not include Copper, Magnesium and Zinc as they are classed non-hazardous

This page has been left blank intentionally.

# Appendix A

Field Sheets (17 pages)

## Appendix A Field Sheets (17 pages)

**Emission Measurement Calculations Spreadsheet****OneSteel Hexham**

AECOM's Project Number: 60493017

Emission Source: Shredder Stack

Date Sampled: 18-Sep-18

<b>ANALYTE(S)</b>	<b>METHOD</b>
Fine Particulate (PM10)	NSW EPA OM - 5
Total Particulate	NSW EPA TM - 15
Hazardous Substances (Metals)	NSW EPA TM - 12, 13 & 14

Observations made during testing period:

Sampling Performed By:

  
Cye Buckland  
for Julian Ward

ANZ

**Emission Measurement Calculations Spreadsheet**

Q4AN(EV)-332-FM31

**STACK ANALYSIS - PRE-SAMPLING**

Date: 18-Sep-18  
 Client: OneSteel Hexham  
 AECOM's Project No: 60493017  
 Stack/Duct Description: Shredder Stack  
 Test 1: Fine Particulate (PM10)  
 Test 2: Total Particulate  
 Test 3: Hazardous Substances (Metals)

Measurement/Observations				
Stack Internal Dimensions:				
Diameter	760 mm		Cross Sectional Area	0.45 m <sup>2</sup>
OR	Length	Width		
Length/Width (mm)			Minimum No. of	
Equivalent Diameter	N/A	mm	sampling points=	12
Distance from sampling plane to nearest disturbances:			Total No. of sampling points =	12
Upstream (m) =	5		PM2.5/10=	12
No. Diameters =	6.6		No. of sampling traverses/ports sampled =	2
Type of Upstream Disturbance:	Fan Entry		PM2.5/10=	2
Downstream (m) =	2		No. of sampling points on each traverse/port =	6
No. Diameters =	2.6		PM2.5/10=	6
Type of Down Stream Disturbance:	Stack Exit			
Position of each sampling point, for each traverse:			Exclusion of any sample point numbers - comments:	
	A	B	PM10/2.5 A	PM2.5/10 B
No.	Distance from wall	S-type Pitot distances	Distance from wall	S-Type Pitot distances
1	33	3	33	3
2	111	81	111	81
3	225	195	225	195
4	535	505	535	505
5	649	619	649	619
6	727	697	727	697
7				
8				
9				
10			Check of total points against minimum, (yes/no) - comments:	
11				
12				
13				
14				
15				
16				
17				
18				
19				
20			General Comments:	
Signed: <i>G. Burkland</i>			Checked: <i>[Signature]</i>	



ANZ

**Emission Measurement Calculations Spreadsheet**

Q4AN(EV)-332-FM31

**STACK ANALYSIS - GAS COMPOSITION AND DENSITY PRE-SAMPLING**

Date: 18-Sep-18  
 Client: OneSteel Hexham  
 AECOM's Project No: 60493017  
 Stack/Duct Description: Shredder Stack  
 Test 1: Fine Particulate (PM10)  
 Test 2: Total Particulate  
 Test 3: Hazardous Substances (Metals)

Sampling time start: 10:40		Sampling port No.: 1		
Measurement No.	Time sampled	CO (ppm), (dry)	O <sub>2</sub> (%), (dry)	CO <sub>2</sub> (%), (dry)
1	10:40	0	20.9	0.0
2	10:41	0	20.9	0.0
3	10:42	0	20.9	0.0
4	10:43	0	20.9	0.0
5	10:44	0	20.9	0.0
6	10:45	0	20.9	0.0
7	10:46	0	20.9	0.0
8	10:47	0	20.9	0.0
Averages:		0.0 ppm	20.9 %	0.0 %

Moisture content (M3): 0.99  
 Moisture percentage (M2): 1.30 %

Measurements

CO: 0.0000 %,(dry)	N <sub>2</sub> : 79.1 %,(dry)
CO <sub>2</sub> : 0.0 %,(dry)	O <sub>2</sub> : 20.9 %,(dry)
Gas Compositions converted to wet basis:	
CO: 0.0000 %,(wet)	N <sub>2</sub> : 78.1 %,(wet)
CO <sub>2</sub> : 0.0 %,(wet)	O <sub>2</sub> : 20.6 %,(wet)
H <sub>2</sub> O: 1.30 % (=M2)	
Therefore, stack gas density (GD) = 1.28 kg/m <sup>3</sup> (0°C, wet, 1 atm pressure)	
Therefore, stack gas density (GD) = 1.29 kg/m <sup>3</sup> (0°C, dry, 1 atm pressure)	

ANZ

**Emission Measurement Calculations Spreadsheet**

Q4AN(EV)-332-FM31

**STACK ANALYSIS - GAS COMPOSITION AND DENSITY POST-SAMPLING**

Date: 18-Sep-18  
 Client: OneSteel Hexham  
 AECOM's Project No: 60493017  
 Stack/Duct Description: Shredder Stack  
 Test 1: Fine Particulate (PM10)  
 Test 2: Total Particulate  
 Test 3: Hazardous Substances (Metals)

Sampling time start: 12:00		Sampling port No.: 1		
Measurement No.	Time sampled	CO (ppm), (dry)	O <sub>2</sub> (%), (dry)	CO <sub>2</sub> (%), (dry)
1	12:00	0	20.9	0.0
2	12:01	0	20.9	0.0
3	12:02	0	20.9	0.0
4	12:03	0	20.9	0.0
5	12:04	0	20.9	0.0
6	12:05	0	20.9	0.0
7	12:06	0	20.9	0.0
8	12:07	0	20.9	0.0
Averages:		0.0 ppm	20.9 %	0.0 %

Moisture content (M3): 0.99  
 Moisture percentage (M2): 1.17 %

Measurements

CO: 0.0000 %,(dry)	N <sub>2</sub> : 79.1 %,(dry)
CO <sub>2</sub> : 0.0 %,(dry)	O <sub>2</sub> : 20.9 %,(dry)
Gas Compositions converted to wet basis:	
CO: 0.0000 %,(wet)	N <sub>2</sub> : 78.2 %,(wet)
CO <sub>2</sub> : 0.0 %,(wet)	O <sub>2</sub> : 20.7 %,(wet)
H <sub>2</sub> O: 1.17 % (=M2)	
Therefore, stack gas density (GD) = 1.28 kg/m <sup>3</sup> (0°C, wet, 1 atm pressure)	
Therefore, stack gas density (GD) = 1.29 kg/m <sup>3</sup> (0°C, dry, 1 atm pressure)	

Emission Measurement Calculations Spreadsheet

**Stack Analysis - Pre Sampling Pitot Tube and Temperature Traverses**

Date: 18-Sep-18  
 Client: OneSteel Hexham  
 AECOM's Project No: 60493017  
 Stack/Duct Description: Shredder Stack  
 Test 1: Fine Particulate (PM10)  
 Test 2: Total Particulate  
 Test 3: Hazardous Substances (Metals)

Time :		10:35		Barometric Pressure :	1020	hPa
Page No. :		1 of 1		Pitot Correction Factor :	0.84	
Sampling Port No:		1 to 2		Stack Gas Density:	1.28	kg/m <sup>3</sup>
Pitot Tube Type :		S		(0 °C, Wet, 1 Atm)		
Sampling Position No.	Distance from far wall (mm)	Max. Differential Pressure ΔP, kilo Pascals	Max Temp. °C	Max Temp. (Ts) K	Corrected Velocity (Vs) m/s	
1/1	3	0.020	26.3	299.5	4.9	
1/2	81	0.023	26.4	299.6	5.2	
1/3	195	0.023	26.4	299.6	5.2	
1/4	505	0.023	26.4	299.6	5.2	
1/5	619	0.025	26.4	299.6	5.4	
1/6	697	0.019	26.3	299.5	4.7	
2/1	3	0.021	26.3	299.5	5.0	
2/2	81	0.025	26.4	299.6	5.4	
2/3	195	0.025	26.4	299.6	5.4	
2/4	505	0.029	26.4	299.6	5.9	
2/5	619	0.025	26.4	299.6	5.4	
2/6	697	0.033	26.3	299.5	6.3	
Average			26.4	299.6	5.3	

Static Pressure (Dwyer) (Pa): kPa  
 Static Pressure (U-tube, if required) : -1.8 mm  
 Absolute pressure in stack (hPa) : 1019.82 hPa







Emission Measurement Calculations Spreadsheet

Stack Analysis - Post Sampling Pitot Tube and Temperature Traverses

Date: 18-Sep-18
Client: OneSteel Hexham
AECOM's Project No: 60493017
Stack/Duct Description: Shredder Stack
Test 1: Fine Particulate (PM10)
Test 2: Total Particulate
Test 3: Hazardous Substances (Metals)

Table with 6 columns: Sampling Position No., Distance from far wall (mm), Max. Differential Pressure ΔP, kilo Pascals, Max Temp. °C, Max Temp. (Ts) K, Corrected Velocity (Vs) m/s. Includes data rows 1/1-1/6 and 2/1-2/6, and an Average row.

Static Pressure (Dwyer) (Pa): kPa
Static Pressure (U-tube, if required) : -1.8 mm
Absolute pressure in stack (hPa) : 1019.82 hPa

Emission Measurement Calculations Spreadsheet

Stack Analysis - Hazardous Substances Elemental Analysis Results

Date: 18-Sep-18 Client: OneSteel Hexham  
 AECOM's Project No: 60493017 Stack/Duct Description: Shredder Stack

Metal	Particulate Metals Results	Gaseous Metals Results	Oxidisable Mercury Results		
	Front Half, Filter, Acetone Rinses and Acid Rinses (mg). Containers 1, 2 and 3	Back Half, Impingers + Acid Rinses (mg) Container 4	KO Impinger + Acid Rinses (mg) (5A)	KMnO <sub>4</sub> /H <sub>2</sub> SO <sub>4</sub> + Rinses (mg) (5B)	Residue Rinse 8N HCl (mg) (If Required) (5C)
Antimony	0.0011	0.00055			
Arsenic	0.00046	0.0003			
Beryllium	0.00002	0.0002			
Cadmium	0.00206	0.0001			
Chromium	0.0026	0.0004			
Cobalt	0.00049	0.0003			
Copper	0.00605	<0.0001			
Lead	0.0683	0.0018			
Magnesium	0.0472	0.0138			
Manganese	0.0089	0.0082			
Mercury	0.00003	<0.0001	<0.0001	0.0000513	<0.0001
Nickel	0.00195	<0.0001			
Selenium	<0.00081	0.0004			
Thallium	0.0004	0.00025			
Tin	0.00174	<0.0161			
Vanadium	<0.0042	<0.005			
Zinc	0.46	0.0209			

Note: Where the blank has returned a less than value, half of this value was subtracted from the sample result as a blank correction ie for a blank value of <0.0005, 0.00025 was subtracted from the sample result.

\* Total does not include Copper, Magnesium and Zinc as they are classed non-hazardous

Stack Analysis - Hazardous Substances Elemental Analysis Results Continued

Date: 18-Sep-18 Client: OneSteel Hexham  
 AECOM's Project No: 60493017 Stack/Duct Description: Shredder Stack

Sample	Total Particulate Metals (mg)	Total Particulate Metals (mg/m <sup>3</sup> )	Total Gaseous Metals (mg)	Total Gaseous Metals (mg/m <sup>3</sup> )	Total Oxidisable Mercury (mg)	Total Oxidisable Mercury (mg/m <sup>3</sup> )	Total (mg)	Total (mg/m <sup>3</sup> )	Mass Emission Rate (mg/s)
Antimony	0.0011	0.000845	0.00055	0.000423			0.0017	0.00131	0.00287
Arsenic	0.00046	0.000353	0.0003	0.00023			0.00076	0.000584	0.00128
Beryllium	0.00002	0.0000154	0.0002	0.000154			0.00022	0.000169	0.00037
Cadmium	0.00206	0.00158	0.0001	0.0000768			0.0022	0.00169	0.0037
Chromium	0.0026	0.002	0.0004	0.000307			0.003	0.0023	0.00503
Cobalt	0.00049	0.000376	0.0003	0.00023			0.00079	0.000607	0.00133
Copper	0.00605	0.00465	<0.0001	<0.0000768			0.0061	0.00469	0.0103
Lead	0.0683	0.0525	0.0018	0.00138			0.07	0.0538	0.118
Magnesium	0.0472	0.0363	0.0138	0.0106			0.061	0.0469	0.103
Manganese	0.0089	0.00684	0.0082	0.0063			0.017	0.0131	0.0287
Mercury	0.00003	0.000023	<0.0001	<0.0000768	0.0000513	0.0000394	0.000081	0.0000622	0.000136
Nickel	0.00195	0.0015	<0.0001	<0.0000768			0.002	0.00154	0.00337
Selenium	<0.00081	<0.000622	0.0004	0.000307			0.0004	0.000307	0.000672
Thallium	0.0004	0.000307	0.00025	0.000192			0.00065	0.000499	0.00109
Tin	0.00174	0.00134	<0.0161	<0.0124			0.0017	0.00131	0.00287
Vanadium	<0.0042	<0.00323	<0.005	<0.00384			<0.0001	<0.0000768	<0.000168
Zinc	0.46	0.353	0.0209	0.0161			0.48	0.369	0.807
Total Hazardous Metals*	0.0863	0.0663	0.0125	0.0096	0.0000513	0.0000394	0.101	0.077	0.169
Total Metals	0.601	0.462	0.0472	0.0363			0.648	0.498	1.09

\* Total does not include Copper, Magnesium and Zinc as they are classed non-hazardous



**STACK ANALYSIS - FINAL CALCULATIONS**

**Fine Particulate (PM10)**

(Calculations performed in accordance with relevant test method as defined on cover page)

Date: 18-Sep-18 Client: OneSteel Hexham  
 AECOM's Project No: 60493017 Stack/Duct Description: Shredder Stack

(A) Sample gas volume at standard conditions

Metered volume (MV<sub>3</sub>): 1.0130 m<sup>3</sup> Average barometric pressure (P<sub>BARO</sub>) 1020 hPa  
 Average gas meter temp. (T<sub>M,2</sub>): 24.7 °C 297.9 K Average pressure at meter (P<sub>M,2</sub>) 1020.00 hPa  
 Sample gas volume (MV<sub>4</sub>); (0°C, dry gas, 1 atm pressure): 0.9352 m<sup>3</sup>

(B) PM10 concentration at standard conditions

Blank thimble No.: 0 Blank weight: g  
 Thimble No. used: T588 PM10 Weight: 0.002 g  
 Final PM10 Weight (M<sub>p1</sub>): 0.00200 g  
 PM10 Concentration (C1): =M<sub>p1</sub>/MV<sub>4</sub>= 0.0021 g/m<sup>3</sup> (0°C, dry gas, 1atm pressure)

CO<sub>2</sub> Basis 12 % ;and C<sub>2</sub> = 2.1 mg/m<sup>3</sup> (0°C, dry gas, 1atm pressure)  
 Average CO<sub>2</sub> %: 0.0 %

Therefore, C<sub>c</sub>: = C<sub>a</sub> x 12/CO<sub>2</sub>% = 0.0021 g/m<sup>3</sup> (0°C, dry gas, 1atm pressure, 12% CO<sub>2</sub>)  
 ;and C<sub>c1</sub> = 2.1 mg/m<sup>3</sup> (0°C, dry gas, 1atm pressure, 12% CO<sub>2</sub>)

O<sub>2</sub> Basis 7 %  
 Average O<sub>2</sub> %: 20.9 %  
 Therefore, C<sub>b</sub>: =C<sub>a</sub> x (21 - O<sub>2ref</sub>%)/(21 - O<sub>2mea</sub>%) 0.29 g/m<sup>3</sup> (0°C, dry gas, 1atm pressure, 7% O<sub>2</sub>)  
 ;and C<sub>b1</sub> = 290 mg/m<sup>3</sup> (0°C, dry gas, 1atm pressure, 7% O<sub>2</sub>)

(C) Moisture content

Silica Gel Number: G042  
 V<sub>v</sub> = 10.3 g (from laboratory report) V<sub>w</sub> = -5 mL (=grams) (recorded on Laboratory Form 108)  
 Volume of Water Vapour Condensed (V<sub>wc(std)</sub>) = -0.0067  
 Volume of Water Vapour Condensed (V<sub>wsg(std)</sub>) = 0.0138  
 Therefore, B<sub>ws</sub> = 
$$\frac{(V_{wc(std)}+V_{wsg(std)})}{(V_{wc(std)}+V_{wsg(std)}+V_{m(std)})}$$
  
 B<sub>ws</sub> = 0.75 %

**STACK ANALYSIS - FINAL CALCULATIONS CONTINUED**

**Fine Particulate (PM10)**

(D) Gas Composition and Density (Re-calculation)

- (i) Initial gas density for sampling: 1.28 kg/m<sup>3</sup> (from Laboratory Form 107)
- (ii) Re-calculated gas density based on moisture content in (c):
  - 1.28 kg/m<sup>3</sup> (0°C, wet, 1 atm pressure)
  - 1.29 kg/m<sup>3</sup> (0°C, dry, 1 atm pressure)
- (iii) Gas density at stack conditions =
 
$$(ii) \times \frac{(273.2)}{(273.2+T_s)} \times \frac{(P_s)}{(1013.25)}$$

= 1.175 kg/m<sup>3</sup> (stack conditions, wet)

(E) Gas Velocities

- (i) Average of pre-sampling velocities: 5.33 m/s
  - (ii) Average of post-sampling velocities: 5.33 m/s
  - (iii) Average of while-sampling velocities: N/A m/s
  - (iv) Overall average of pre-sampling and post-sampling velocities (Vs):
    - 5.33 m/s (stack conditions, wet)
    - N/A m/s (stack conditions, wet)
- (Note: (Vs) is from all individual data, **not** from (i) and (ii) alone.)

(F) Volumetric Flowrates (Reference Method US-EPA Method 2, NSW-EPA TM-2)

Q<sub>stack</sub> = V<sub>s</sub> x A = 2.42 m<sup>3</sup>/s (stack conditions)

$$Q_{std} = Q_{stack} \times \frac{P_s}{(P_{std})} \times \frac{(T_{std})}{(T_s)} \times \frac{(100 - B_w)}{100}$$

Q<sub>std</sub> = 2.2 m<sup>3</sup>/s (0°C, dry gas, 1 atm pressure)

(G) Mass Emission Rate

R<sub>m</sub> = C<sub>1a</sub> x Q<sub>std</sub> = 0.0046 g/s (0°C, dry gas, 1 atm pressure )

= 4.6 mg/s (0°C, dry gas, 1 atm pressure )

**STACK ANALYSIS - FINAL CALCULATIONS**

**Total Particulate**

(Calculations performed in accordance with relevant test method as defined on cover page)

Date: 18-Sep-18 Client: OneSteel Hexham  
 AECOM's Project No: 60493017 Stack/Duct Description: Shredder Stack

(A) Sample gas volume at standard conditions

Metered volume (MV <sub>3</sub> ):	0.6723 m <sup>3</sup>	Average barometric pressure (P <sub>BARO</sub> ):	1020 hPa
Average gas meter temp. (T <sub>M,2</sub> ):	25.0 °C	Average pressure at meter (P <sub>M,2</sub> ):	1020.00 hPa
	298.2 K		
Sample gas volume (MV <sub>4</sub> ); (0°C, dry gas, 1 atm pressure):	0.6200 m <sup>3</sup>		

(B) Total Particulate concentration at standard conditions

Blank thimble No.:		Blank weight:	g
Thimble No. used:	T589	Total Particulate Weight:	0.0193 g
Final Total Particulate Weight (Mp1):	0.01930 g		
Total Particulate Concentration (C1):	=M <sub>p1</sub> /MV <sub>4</sub> =		0.031 g/m <sup>3</sup> (0°C, dry gas, 1atm pressure)

CO <sub>2</sub> Basis:	12 %	;and C <sub>2</sub> =	31 mg/m <sup>3</sup> (0°C, dry gas, 1atm pressure)
Average CO <sub>2</sub> %:	0.0 %		

Therefore, C <sub>c</sub> :	= C <sub>a</sub> x 12/CO <sub>2</sub> % =	0.031 g/m <sup>3</sup> (0°C, dry gas, 1atm pressure, 12% CO <sub>2</sub> )
	;and C <sub>c1</sub> =	31 mg/m <sup>3</sup> (0°C, dry gas, 1atm pressure, 12% CO <sub>2</sub> )

O <sub>2</sub> Basis:	7 %
Average O <sub>2</sub> %:	20.9 %

Therefore, C <sub>b</sub> :	=C <sub>a</sub> x (21 - O <sub>2ref</sub> %)/(21 - O <sub>2mea</sub> %)	4.3 g/m <sup>3</sup> (0°C, dry gas, 1atm pressure, 7% O <sub>2</sub> )
	;and C <sub>b1</sub> =	4300 mg/m <sup>3</sup> (0°C, dry gas, 1atm pressure, 7% O <sub>2</sub> )

(C) Moisture content

Silica Gel Number:	G101		
V <sub>v</sub> =	12.2 g (from laboratory report)	V <sub>w</sub> =	-6 mL (=grams) (recorded on Laboratory Form 108)
Volume of Water Vapour Condensed (V <sub>wc(std)</sub> ) =	-0.0080		
Volume of Water Vapour Condensed (V <sub>wsg(std)</sub> ) =	0.0163		
Therefore, B <sub>ws</sub> =	$\frac{(V_{wc(std)} + V_{wsg(std)})}{(V_{wc(std)} + V_{wsg(std)} + V_{m(std)})}$		
B <sub>ws</sub> =	1.32 %		

**STACK ANALYSIS - FINAL CALCULATIONS CONTINUED**

**Total Particulate**

(D) Gas Composition and Density (Re-calculation)

- (i) Initial gas density for sampling: 1.28 kg/m<sup>3</sup> (from Laboratory Form 107)
- (ii) Re-calculated gas density based on moisture content in (c):
  - 1.28 kg/m<sup>3</sup> (0°C, wet, 1 atm pressure)
  - 1.29 kg/m<sup>3</sup> (0°C, dry, 1 atm pressure)
- (iii) Gas density at stack conditions = (ii) x  $\frac{(273.2)}{(273.2+T_s)} \times \frac{(P_s)}{(1013.25)}$   
 = 1.175 kg/m<sup>3</sup> (stack conditions, wet)

(E) Gas Velocities

- (i) Average of pre-sampling velocities: 5.33 m/s
  - (ii) Average of post-sampling velocities: 5.33 m/s
  - (iii) Average of while-sampling velocities: N/A m/s
  - (iv) Overall average of pre-sampling and post-sampling velocities (Vs):
    - 5.33 m/s (stack conditions, wet)
    - N/A m/s (stack conditions, wet)
- (Note: (Vs) is from all individual data, **not** from (i) and (ii) alone.)

(F) Volumetric Flowrates (Reference Method US-EPA Method 2, NSW-EPA TM-2)

Q<sub>stack</sub> = V<sub>s</sub> x A = 2.42 m<sup>3</sup>/s (stack conditions)

Q<sub>std</sub> = Q<sub>stack</sub> x  $\frac{P_s}{(P_{std})} \times \frac{(T_{std})}{(T_s)} \times \frac{(100 - B_w)}{100}$

Q<sub>std</sub> = 2.2 m<sup>3</sup>/s (0°C, dry gas, 1 atm pressure)

(G) Mass Emission Rate

R<sub>m</sub> = C<sub>1a</sub> x Q<sub>std</sub> = 0.068 g/s (0°C, dry gas, 1 atm pressure )  
 = 68 mg/s (0°C, dry gas, 1 atm pressure )

**STACK ANALYSIS - FINAL CALCULATIONS**

**Hazardous Substances (Metals)**

(Calculations performed in accordance with relevant test method as defined on cover page)

Date: 18-Sep-18 Client: OneSteel Hexham  
 AECOM's Project No: 60493017 Stack/Duct Description: Shredder Stack

(A) Sample gas volume at standard conditions

Metered volume (MV <sub>3</sub> ):	1.4138 m <sup>3</sup>	Average barometric pressure (P <sub>BARO</sub> ):	1020 hPa
Average gas meter temp. (T <sub>M,2</sub> ):	25.5 °C	Average pressure at meter (P <sub>M,2</sub> ):	1020.00 hPa
	298.7 K		
Sample gas volume (MV <sub>4</sub> ); (0°C, dry gas, 1 atm pressure):	1.3017 m <sup>3</sup>		

(B) Metals concentration at standard conditions

Blank thimble No.:		Blank weight:	g
Thimble No. used:	0	Metals Weight:	0.000101 g
Final Metals Weight (Mp1):	0.00010 g		
Metals Concentration (C1):	=Mp1/MV <sub>4</sub> =		0.000077 g/m <sup>3</sup> (0°C, dry gas, 1atm pressure)

CO<sub>2</sub> Basis 12 % ;and C<sub>2</sub> = 0.077 mg/m<sup>3</sup> (0°C, dry gas, 1atm pressure)

Average CO<sub>2</sub>%; 0.0 %

Therefore, C<sub>c</sub>: = C<sub>a</sub> x 12/CO<sub>2</sub>% = 0.000077 g/m<sup>3</sup> (0°C, dry gas, 1atm pressure, 12% CO<sub>2</sub>)  
 ;and C<sub>c1</sub> = 0.077 mg/m<sup>3</sup> (0°C, dry gas, 1atm pressure, 12% CO<sub>2</sub>)

O<sub>2</sub> Basis 7 %

Average O<sub>2</sub>%; 20.9 %

Therefore, C<sub>b</sub>: =C<sub>a</sub> x (21 - O<sub>2ref</sub>%)/(21 - O<sub>2mea</sub>%) = 0.011 g/m<sup>3</sup> (0°C, dry gas, 1atm pressure, 7% O<sub>2</sub>)  
 ;and C<sub>b1</sub> = 11 mg/m<sup>3</sup> (0°C, dry gas, 1atm pressure, 7% O<sub>2</sub>)

(C) Moisture content

Silica Gel Number:	G068		
V <sub>v</sub> =	11.1 g (from laboratory report)	V <sub>w</sub> =	3 mL (=grams) (recorded on Laboratory Form 108)
Volume of Water Vapour Condensed (V <sub>wc(std)</sub> ) =	0.0040		
Volume of Water Vapour Condensed (V <sub>wsg(std)</sub> ) =	0.0148		

Therefore, B<sub>ws</sub> =  $\frac{(V_{wc(std)} + V_{wsg(std)})}{(V_{wc(std)} + V_{wsg(std)} + V_{m(std)})}$

B<sub>ws</sub> = 1.42 %

**STACK ANALYSIS - FINAL CALCULATIONS CONTINUED****Hazardous Substances (Metals)****(D) Gas Composition and Density (Re-calculation)**

(i) Initial gas density for sampling:	1.28 kg/m <sup>3</sup> (from Laboratory Form 107)
(ii) Re-calculated gas density based on moisture content in (c):	1.28 kg/m <sup>3</sup> (0°C, wet, 1 atm pressure) 1.29 kg/m <sup>3</sup> (0°C, dry, 1 atm pressure)
(iii) Gas density at stack conditions =	(ii) x $\frac{(273.2)}{(273.2+T_s)}$ x $\frac{(P_s)}{(1013.25)}$
=	1.175 kg/m <sup>3</sup> (stack conditions, wet)

**(E) Gas Velocities**

(i) Average of pre-sampling velocities:	5.33 m/s
(ii) Average of post-sampling velocities:	5.33 m/s
(iii) Average of while-sampling velocities:	N/A m/s
(iv) Overall average of pre-sampling and post-sampling velocities (Vs):	5.33 m/s (stack conditions, wet) N/A m/s (stack conditions, wet)
<b>(Note: (Vs) is from all individual data, not from (i) and (ii) alone.)</b>	

**(F) Volumetric Flowrates (Reference Method US-EPA Method 2, NSW-EPA TM-2)**

Q <sub>stack</sub> =	V <sub>s</sub> x A =	2.42 m <sup>3</sup> /s (stack conditions)
Q <sub>std</sub> =	Q <sub>stack</sub> x $\frac{P_s}{(P_{std})}$ x $\frac{(T_{std})}{(T_s)}$ x $\frac{(100 - B_w)}{100}$	
Q <sub>std</sub> =	2.2 m <sup>3</sup> /s (0°C, dry gas, 1 atm pressure)	

**(G) Mass Emission Rate**

R <sub>m</sub> =	C <sub>1a</sub> x Q <sub>std</sub> =	0.00017 g/s (0°C, dry gas, 1 atm pressure )
	=	0.17 mg/s (0°C, dry gas, 1 atm pressure )

**Emission Measurement Calculations Spreadsheet**

<b>EMISSION MONITORING RESULTS, SHREDDER STACK</b> <b>ONESTEEL HEXHAM</b> 18-Sep-18 FINE PARTICULATE (PM10) TOTAL PARTICULATE HAZARDOUS SUBSTANCES (METALS)		
<b>Sampling Conditions:</b>		
Stack internal diameter at test location	760 mm	
Stack gas temperature (average)	26.4 °C	299.6 K
Stack pressure (average)	1020 hPa	
Stack gas velocity (average, stack conditions)	5.3 m/s	
Stack gas flowrate (stack conditions)	2.4 m <sup>3</sup> /s	
Stack gas flowrate (0°C, dry gas, 1 atm pressure)	2.2 m <sup>3</sup> /s	
<b>Fine Particulate (PM10) Testing</b>		
Test Period	10:45	- 12:15
Fine Particulate (PM10) Mass	2.0 mg	
Gas Volume Sampled	0.94 m <sup>3</sup>	
Fine Particulate (PM10) Emission*1	2.1 mg/m <sup>3</sup>	
Fine Particulate (PM10) Mass Emission Rate*2	4.6 mg/s	
Regulatory Limit	N/A	
<b>Total Particulate Testing</b>		
Test Period	10:45	- 12:15
Total Particulate Mass	19 mg	
Gas Volume Sampled	0.62 m <sup>3</sup>	
Total Particulate Emission*1	31 mg/m <sup>3</sup>	
Total Particulate Mass Emission Rate*2	68 mg/s	
Regulatory Limit	100 mg/m <sup>3</sup>	
<b>Hazardous Substances (Metals) Testing</b>		
Test Period	10:45	- 12:15
Hazardous Substances (Metals) Mass	0.10 mg	
Gas Volume Sampled	1.3 m <sup>3</sup>	
Hazardous Substances (Metals) Emission*1	0.077 mg/m <sup>3</sup>	
Hazardous Substances (Metals) Mass Emission Rate*2	0.17 mg/s	
Regulatory Limit	N/A	
<b>Moisture Content (%)</b>	1.4	
<b>Gas Density (dry at 1 atmosphere)</b>	1.29 kg/m <sup>3</sup>	
<b>Dry Molecular Weight</b>	28.8 g/g-mole	

Notes \*1 Emission concentration at Standard conditions of 0°C, 1 atm, dry gas

\*2 Mass emission rate determined from pre and post test sampling flow measurements and the respective test moisture content. See Q<sub>std</sub> in field sheets and final calculations "Stack Analysis - Final Calculations" for each test.





# Appendix B

Laboratory Results  
(8 pages)

## Appendix B Laboratory Results (8 pages)

# Steel River Testing

5/11 McIntosh Drive, Mayfield West, NSW 2304  
Phone: 02 49677880

## STACK EMISSION - MOISTURE REPORT

**Origin:** AECOM - Newcastle  
**Project:** 60493017  
**Report :** 16962-0-M Page 1 of 1  
**Description :** Stack Emission Samples  
Received: 24-Sep-18  
**Date :** 25-Sep-18  
**Report To :** Colin Clarke  
17 Warabrook Blvd, Warabrook NSW 2304  
**Copy to:** FILE

---

Jar ID	Moisture (g)
G042	10.3
G068	11.1
G101	12.2



NATA Accredited Laboratory 18079  
Accredited for compliance with  
ISO/IEC 17025 - Testing

**Reported By:** J. Campbell  
Jason Campbell - Manager

Determined in Accordance With:  
Moisture content in stack gases by gravimetric  
using in-house M301  
Refer Form F422 - Measurement Uncertainty

# Steel River Testing

5/11 McIntosh Drive, Mayfield West, NSW 2304

Phone: 02 49677880

## STACK EMISSION - PARTICULATES REPORT

**Origin:** AECOM - Newcastle

**Project:** 60493017

**Report :** 16962-0-P

Page 1 of 1

**Description :** Stack Emission Samples

Received: 24-Sep-18

**Date :** 25-Sep-18

**Report To :** Colin Clarke

17 Warabrook Blvd, Warabrook NSW 2304

**Copy to:** FILE

---

Thimble ID		Volume (mL)	Total Particulate Matter (g)
T588	Filter	-	0.0020
T589	Filter	-	0.0193



NATA Accredited Laboratory 18079

Accredited for compliance with  
ISO/IEC 17025 - Testing

Note : *Sampled by Client*

**Reported By:** J. Campbell

Jason Campbell - Manager

Determined in Accordance With:  
Particulate matter - total in stack gases by  
gravimetric using in-house M300;  
Acetone/Water Rinse using AS4323.2  
Refer Form F422 - Measurement Uncertainty

CLIENT DETAILS

Contact **Cye Buckland**  
 Client **AECOM Australia Pty Ltd**  
 Address **17 Warabrook Boulevard  
 Warabrook  
 SYDNEY NSW 2304**

Telephone **02 8295 3600**  
 Facsimile **02 8934 0001**  
 Email **cye.buckland@aecom.com**

Project **(Not specified)**  
 Order Number **60493017/3.1**  
 Samples **12**

LABORATORY DETAILS

Manager **Adam Atkinson**  
 Laboratory **SGS Melbourne EH&S**  
 Address **10/585 Blackburn Road  
 Notting Hill Victoria 3168**

Telephone **+61395743200**  
 Facsimile **+61395743399**  
 Email **Au.SampleReceipt.Melbourne@sgs.com**

SGS Reference **ME308220 R0**  
 Date Received **21 Sep 2018**  
 Date Reported **02 Oct 2018**

COMMENTS

Accredited for compliance with ISO/IEC 17025 - Testing. NATA accredited laboratory 2562(14420).

SIGNATORIES

*MING*

Weiming Dai  
 Inorganic Supervisor

*Rzhang*

Ryan Zhang  
 Team Leader

Sample Number	ME308220.001	ME308220.002	ME308220.003	ME308220.004
Sample Matrix	Filter	Filter	Impinger Solution	Impinger Solution
Sample Date	18 Sep 2018	18 Sep 2018	18 Sep 2018	18 Sep 2018
Sample Name	Metals No. 1	Metals No. 12	Metals No. 3	Metals No. 4

Parameter Units LOR  
 Metals in Filters M29 ETC MA-1400.FL.M29.02 USEPA M29 Method: EPA29\_FILT Tested: 26/9/2018

Parameter	Units	LOR	ME308220.001	ME308220.002	ME308220.003	ME308220.004
Sb	µg total	0.05	0.64	0.14	-	-
As	µg total	0.05	0.82	0.66	-	-
Be	µg total	0.05	0.16	0.14	-	-
Cd	µg total	0.05	1.9	0.14	-	-
Cr	µg total	0.05	3.6	2.0	-	-
Co	µg total	0.05	0.32	0.13	-	-
Cu	µg total	0.05	3.5	0.35	-	-
Pb	µg total	0.05	33	1.0	-	-
Mg	µg total	0.05	250	220	-	-
Mn	µg total	0.05	6.8	1.9	-	-
Hg	µg total	0.05	0.08	<0.05	-	-
Ni	µg total	0.05	1.5	<0.05	-	-
Se	µg total	0.05	0.35	0.41	-	-
Tl	µg total	0.05	0.20	0.10	-	-
Sn	µg total	0.05	1.4	0.26	-	-
V	µg total	0.25	1.4	1.2	-	-
Zn	µg total	0.05	6100	5800	-	-

Metals in Impingers M29 ETC MA-1400.IMP.M29.06 (µg total) Method: EPA29\_METIMP Tested: 2/10/2018

Parameter	Units	LOR	ME308220.001	ME308220.002	ME308220.003	ME308220.004
Sb	µg total	0.1	-	-	0.6	0.6
As	µg total	0.1	-	-	0.4	0.4
Be	µg total	0.1	-	-	0.2	0.4
Cd	µg total	0.1	-	-	0.4	0.5
Cr	µg total	0.1	-	-	1.2	0.7
Co	µg total	0.1	-	-	0.4	0.4
Cu	µg total	0.1	-	-	2.9	<0.1
Pb	µg total	0.1	-	-	39	4.5
Mg	µg total	0.1	-	-	20	18
Mn	µg total	0.1	-	-	4.4	8.9
Hg	µg total	0.1	-	-	<0.1	<0.1
Ni	µg total	0.1	-	-	0.5	<0.1
Se	µg total	0.1	-	-	0.4	1.0
Tl	µg total	0.1	-	-	0.3	0.3
Sn	µg total	0.1	-	-	0.7	16
V	µg total	0.1	-	-	1.1	3.2
Zn	µg total	0.1	-	-	160	23
Sample Volume*	mL	-	-	-	90	300

	Sample Number	ME308220.005	ME308220.006	ME308220.007	ME308220.008
	Sample Matrix	Impinger	Impinger	Impinger	Impinger
	Sample Date	Solution	Solution	Solution	Solution
	Sample Name	18 Sep 2018	18 Sep 2018	18 Sep 2018	18 Sep 2018
		Metals No. 8A	Metals No. 9	Metals No. 5A	Metals No. 6C
Parameter	Units	LOR			

Metals in Filters M29 ETC MA-1400.FL.M29.02 USEPA M29 Method: EPA29\_FILT Tested: 1/10/2018

Parameter	Units	LOR	ME308220.005	ME308220.006	ME308220.007	ME308220.008
Sb	µg total	0.05	-	-	-	-
As	µg total	0.05	-	-	-	-
Be	µg total	0.05	-	-	-	-
Cd	µg total	0.05	-	-	-	-
Cr	µg total	0.05	-	-	-	-
Co	µg total	0.05	-	-	-	-
Cu	µg total	0.05	-	-	-	-
Pb	µg total	0.05	-	-	-	-
Mg	µg total	0.05	-	-	-	-
Mn	µg total	0.05	-	-	-	-
Hg	µg total	0.05	-	-	-	-
Ni	µg total	0.05	-	-	-	-
Se	µg total	0.05	-	-	-	-
Tl	µg total	0.05	-	-	-	-
Sn	µg total	0.05	-	-	-	-
V	µg total	0.25	-	-	-	-
Zn	µg total	0.05	-	-	-	-

Metals in Impingers M29 ETC MA-1400.IMP.M29.06 (ug total) Method: EPA29\_MLTIMP Tested: 26/9/2018

Parameter	Units	LOR	ME308220.005	ME308220.006	ME308220.007	ME308220.008
Sb	µg total	0.1	<0.1	<0.1	-	-
As	µg total	0.1	0.1	<0.1	-	-
Be	µg total	0.1	0.2	<0.1	-	-
Cd	µg total	0.1	0.1	0.3	-	-
Cr	µg total	0.1	0.2	0.1	-	-
Co	µg total	0.1	0.1	<0.1	-	-
Cu	µg total	0.1	<0.1	<0.1	-	-
Pb	µg total	0.1	2.7	<0.1	-	-
Mg	µg total	0.1	2.8	1.4	-	-
Mn	µg total	0.1	0.4	0.3	-	-
Hg	µg total	0.1	<0.1	<0.1	<0.1	<0.1
Ni	µg total	0.1	<0.1	<0.1	-	-
Se	µg total	0.1	0.4	0.2	-	-
Tl	µg total	0.1	<0.1	<0.1	-	-
Sn	µg total	0.1	0.1	16	-	-
V	µg total	0.1	3.0	2.0	-	-
Zn	µg total	0.1	<0.1	2.1	-	-
Sample Volume*	mL	-	310	200	100	240

Sample Number	ME308220.009	ME308220.010	ME308220.011	ME308220.012
Sample Matrix	Impinger	Impinger	KMnO4	KMnO4
Sample Date	Solution	Solution	18 Sep 2018	18 Sep 2018
Sample Name	18 Sep 2018	18 Sep 2018	Metals No. 5B	Metals No. 10
	Metals No. 8B	Metals No. 11		

Parameter Units LOR  
 Metals in Filters M29 ETC MA-1400.FL.M29.02 USEPA M29 Method: EPA29\_FILT Tested: 1/10/2018

Element	Units	LOR	ME308220.009	ME308220.010	ME308220.011	ME308220.012
Sb	µg total	0.05	-	-	-	-
As	µg total	0.05	-	-	-	-
Be	µg total	0.05	-	-	-	-
Cd	µg total	0.05	-	-	-	-
Cr	µg total	0.05	-	-	-	-
Co	µg total	0.05	-	-	-	-
Cu	µg total	0.05	-	-	-	-
Pb	µg total	0.05	-	-	-	-
Mg	µg total	0.05	-	-	-	-
Mn	µg total	0.05	-	-	-	-
Hg	µg total	0.05	-	-	-	-
Ni	µg total	0.05	-	-	-	-
Se	µg total	0.05	-	-	-	-
Tl	µg total	0.05	-	-	-	-
Sn	µg total	0.05	-	-	-	-
V	µg total	0.25	-	-	-	-
Zn	µg total	0.05	-	-	-	-

Metals in Impingers M29 ETC MA-1400.IMP.M29.06 (ug total) Method: EPA29\_METIMP Tested: 26/9/2018

Element	Units	LOR	ME308220.009	ME308220.010	ME308220.011	ME308220.012
Sb	µg total	0.1	-	-	-	-
As	µg total	0.1	-	-	-	-
Be	µg total	0.1	-	-	-	-
Cd	µg total	0.1	-	-	-	-
Cr	µg total	0.1	-	-	-	-
Co	µg total	0.1	-	-	-	-
Cu	µg total	0.1	-	-	-	-
Pb	µg total	0.1	-	-	-	-
Mg	µg total	0.1	-	-	-	-
Mn	µg total	0.1	-	-	-	-
Hg	µg total	0.1	<0.1	<0.1	0.1	<0.1
Ni	µg total	0.1	-	-	-	-
Se	µg total	0.1	-	-	-	-
Tl	µg total	0.1	-	-	-	-
Sn	µg total	0.1	-	-	-	-
V	µg total	0.1	-	-	-	-
Zn	µg total	0.1	-	-	-	-
Sample Volume*	mL	-	100	250	390	100



MB blank results are compared to the Limit of Reporting  
 LCS and MS spike recoveries are measured as the percentage of analyte recovered from the sample compared the the amount of analyte spiked into the sample.  
 DUP and MSD relative percent differences are measured against their original counterpart samples according to the formula : *the absolute difference of the two results divided by the average of the two results as a percentage*. Where the DUP RPD is 'NA' , the results are less than the LOR and thus the RPD is not applicable.

Metals in Filters M29 ETC MA-1400.FL.M29.02 USEPA M29 Method: EPA29\_FILT

Parameter	QC Reference	Units	LOR	MB	LCS %Recovery
Sb	LB022885	µg total	0.05	<0.05	108%
As	LB022885	µg total	0.05	<0.05	103%
Be	LB022885	µg total	0.05	<0.05	98%
Cd	LB022885	µg total	0.05	<0.05	106%
Cr	LB022885	µg total	0.05	<0.05	100%
Co	LB022885	µg total	0.05	<0.05	109%
Cu	LB022885	µg total	0.05	<0.05	105%
Pb	LB022885	µg total	0.05	<0.05	107%
Mg	LB022885	µg total	0.05	<0.05	105%
Mn	LB022885	µg total	0.05	<0.05	105%
Hg	LB022885	µg total	0.05	<0.05	107%
Ni	LB022885	µg total	0.05	<0.05	104%
Se	LB022885	µg total	0.05	<0.05	95%
Tl	LB022885	µg total	0.05	<0.05	104%
Sn	LB022885	µg total	0.05	<0.05	106%
V	LB022885	µg total	0.25	<0.25	106%
Zn	LB022885	µg total	0.05	<0.05	102%

Metals in Impingers M29 ETC MA-1400.IMP.M29.05 (ug total) Method: EPA29\_METIMP

Parameter	QC Reference	Units	LOR	MB	LCS %Recovery
Sb	LB022889	µg total	0.1	<0.1	108%
As	LB022889	µg total	0.1	<0.1	103%
Be	LB022889	µg total	0.1	<0.1	96%
Cd	LB022889	µg total	0.1	<0.1	105%
Cr	LB022889	µg total	0.1	<0.1	100%
Co	LB022889	µg total	0.1	<0.1	107%
Cu	LB022889	µg total	0.1	<0.1	104%
Pb	LB022889	µg total	0.1	<0.1	108%
Mg	LB022889	µg total	0.1	<0.1	109%
Mn	LB022889	µg total	0.1	<0.1	105%
Hg	LB022889	µg total	0.1	<0.1	
Ni	LB022889	µg total	0.1	<0.1	104%
Se	LB022889	µg total	0.1	<0.1	92%
Tl	LB022889	µg total	0.1	<0.1	107%
Sn	LB022889	µg total	0.1	<0.1	106%
V	LB022889	µg total	0.1	<0.1	107%
Zn	LB022889	µg total	0.1	<0.1	102%
Sample Volume*	LB022889	mL	-	1.0	NA

METHOD

METHODOLOGY SUMMARY

EPA 29

Analysis of acid-leachable metals by Inductively Coupled Plasma-Mass Spectrometer (ICP-MS). This method is based on USEPA 3051A, USEPA M29, and USEPA 6020A.  
 . Filters are digested using the appropriate sample preparation methods.  
 A representative sample is extracted in concentrated acid using microwave heating by the CEM -MarsXPress (with Built-in USEPA method) Microwave Digestion system. The sample and acid are placed in a microwave vessel (TFM), which is then capped and heated in the microwave unit. After cooling, the vessel contents are diluted with DI water, then filtered/settled/centrifuged and analysed by ICP MS.

EPA29

This method covers the analysis of acid-leachable metals by Inductively Coupled Plasma-Mass Spectrometer (ICP-MS). This method is based on USEPA M29, USEPA 3015A and USEPA 6020A.  
 Prior to analysis, samples are be solubilised or digested using the appropriate sample preparation methods.

FOOTNOTES

- IS Insufficient sample for analysis.
- LNR Sample listed, but not received.
- \* NATA accreditation does not cover the performance of this service.
- \*\* Indicative data, theoretical holding time exceeded.

- LOR Limit of Reporting
- ↑↓ Raised or Lowered Limit of Reporting
- QFH QC result is above the upper tolerance
- QFL QC result is below the lower tolerance
- The sample was not analysed for this analyte
- NVL Not Validated

Samples analysed as received.  
 Solid samples expressed on a dry weight basis.

Where "Total" analyte groups are reported (for example, Total PAHs, Total OC Pesticides) the total will be calculated as the sum of the individual analytes, with those analytes that are reported as <LOR being assumed to be zero. The summed (Total) limit of reporting is calculated by summing the individual analyte LORs and dividing by two. For example, where 16 individual analytes are being summed and each has an LOR of 0.1 mg/kg, the "Totals" LOR will be 1.6 / 2 (0.8 mg/kg). Where only 2 analytes are being summed, the "Total" LOR will be the sum of those two LORs.

Some totals may not appear to add up because the total is rounded after adding up the raw values.

If reported, measurement uncertainty follow the ± sign after the analytical result and is expressed as the expanded uncertainty calculated using a coverage factor of 2, providing a level of confidence of approximately 95%, unless stated otherwise in the comments section of this report.

Results reported for samples tested under test methods with codes starting with ARS-SOP, radionuclide or gross radioactivity concentrations are expressed in becquerel (Bq) per unit of mass or volume or per wipe as stated on the report. Becquerel is the SI unit for activity and equals one nuclear transformation per second.

Note that in terms of units of radioactivity:

- a. 1 Bq is equivalent to 27 pCi
- b. 37 MBq is equivalent to 1 mCi

For results reported for samples tested under test methods with codes starting with ARS-SOP, less than (<) values indicate the detection limit for each radionuclide or parameter for the measurement system used. The respective detection limits have been calculated in accordance with ISO 11929.

The QC criteria are subject to internal review according to the SGS QAQC plan and may be provided on request or alternatively can be found here : <http://www.sgs.com.au/~media/Local/Australia/Documents/Technical%20Documents/MP-AU-ENV-QU-022%20QA%20QC%20Plan.pdf>

This document is issued by the Company under its General Conditions of Service accessible at [www.sgs.com/en/Terms-and-Conditions.aspx](http://www.sgs.com/en/Terms-and-Conditions.aspx). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein.

Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client only. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law .

This report must not be reproduced, except in full.

